

CONDITIONS OF USE 使用条件

Maximum operating temperature 120°C。/最大运行温度120°C。

Maximum operating pressure 10 bar。/最大运行压力10 bar。

ATTENTION 注意

All the Thermostatically Controlled Valves are available in 9 different configurations:the order's code has to be created as shown .

出售的所有温控阀有 9 种不同的配置：订货代码如图所示。

■ | STANDARD 样品

Version in the catalogue.
目录里的版本。

■ | TG

Manual head with brass ring.
手动头，带黄铜环。

■ | RC

With soft seal fitting.
带软密封接头。

■ | TRC

With manual head ring and soft seal fitting.
带手动头环和软密封接头。

■ | RCR

With 3/8 M reduced soft seal fitting.
Ø3/8 不带软密封圈。

■ | TGRC

With manual head with brass ring and soft seal fitting.
带手动头，手动头带黄铜环和软密封接头。

■ | T

Manual head.
手动头。



■ | **TRCR**
 manual head and 3/8M reduced soft seal fitting(not available for DN10 & DN20).
 手动头和 03/8 不带软密封圈 (不适用于接口 DN10 和 DN20)。

■ | **TGRCR**
 With manual head with brass ring and 3/8M reduced soft seal fitting(not available for DN10 & DN20).
 带手动头, 手动头带黄铜环和 03/8 不带软密封圈 (不适用于接口 DN10 和 DN20)。



T (TM 3053)



TG (TM 3052)



RC / RCR (AGE 01)

EXAMPLE 参考样品



STANDARD VERSION/标准件
 500440



500440RC



500440TRC





500440RCR



500440TGRC



500440T



500440TRCR



500440TG



500440TGRCR

